

Designations	Boundary dimensions(mm)					Basic load ratings(kN)		Speed rating		Weight	foreign models (reference)	
	d	D	B	Fw	rmin	Cr	Cor	Grease	Oil	(kg)	SKF	FAG
NNU3024X1	120	180	52	135	2	240	450	2500	3200	4.87	-	-
NNU3028	140	210	53	158	2	270	590	2100	2600	6.5	-	-
NNU3030X1	150	225	60	169	2.1	380	700	1900	2350	8.7	-	-
NNU3044X1	220	340	96	246	3	950	1760	950	1250	32.8	-	-
NNU4920	100	140	40	113	1.1	130	280	3400	4200	2.1	NNU4920	NNU4920
NNU4922	110	150	40	123	1.1	140	290	3100	3850	2.2	NNU4922	NNU4922
NNU4924	120	165	45	134.5	1.1	180	340	2800	3500	2.8	NNU4924	NNU4924
NNU4124X2	120	190	80	141	2	370	710	2500	3100	9	-	-
NNU4224X1	120	215	86	139	2.1	570	850	2200	2750	13.6	-	-
NNU4926	130	180	50	146	1.5	220	470	2500	3100	4	NNU4926	NNU4926
NNU4928	140	190	50	156	1.5	280	580	2200	2750	4.2	NNU4928	NNU4928
NNU4028X1-1	140	210	62.5	158	2	370	700	2100	2600	7.9	-	-
NNU4028X1-2	140	210	77.5	158	2	450	950	2100	2600	9.8	-	-
NNU4930	150	210	60	168.5	2	340	730	2000	2500	6.7	NNU4930	NNU4930
NNU4230X1	150	270	120	180	3	930	1710	1600	2000	31.5	-	-
NNU4932	160	220	60	178.5	2	330	680	1900	2350	6.9	NNU4932	NNU4932
NNU4934	170	230	60	188.5	2	340	700	1800	2200	7.25	NNU4934	NNU4934
NNU4936	180	250	69	202	2	400	850	1600	2000	10.5	NNU4936	NNU4936
NNU4938	190	260	69	212	2	420	990	1450	1800	11.5	NNU4938	NNU4938
NNU4940	200	280	80	225	2.1	480	1040	1400	1700	15	NNU4940	NNU4940
NNU4040	200	310	109	234	2.1	670	1440	1350	1700	32.7	-	-
NNU4940X2	200	310	130	229	2.1	1000	2270	1350	1700	38.9	-	-
NNU4240X1	200	360	148	242	4	1520	2890	1000	1250	71.9	-	-
NNU4944	220	300	80	245	2.1	530	1150	1300	1600	18	NNU4944	NNU4944
NNU4948	240	320	80	265	2.1	620	1450	1200	1500	18.5	NNU4948	NNU4948
NNU4952	260	360	100	292	2.1	750	1900	1100	1350	35.8	NNU4952	NNU4952
NNU4952X2	260	370	100	292	2.1	830	2050	1100	1350	37.1	-	-
NNU4956	280	380	100	312	2.1	850	2100	1000	1250	36	NNU4956	NNU4956
NNU4960	300	420	118	339	3	950	2500	900	1150	54.5	NNU4960	NNU4960
NNU4964	320	440	118	359	3	1000	2700	850	1100	58	NNU4964	NNU4964
NNU5036X3	180	270	120	202	2.1	790	1650	1400	1800	25.8	-	-
NNU5048X1	240	360	165	270	3	1310	2950	1150	1420	61.7	-	-